
PHILIPS Lighting



GreenPerform Sleek

DN296B LED15S-6500 PSU WH

Green Perform Sleek luminaire is designed for low dept false ceiling. Slim design with non-integral driver enables installation into low height false ceilings of different thickness and materials. Narrow rim semi-deep recessed design gives high quality lighting for designer ceilings. Highly efficient Electronic driver with high performance LED's ensures the longer life & high performance in this product category. Wide range of CCT's & Lumen packs suitable for various application.

Warnings and Safety

Meant for Indoor Application Only. Should not be used in outdoor environment.

Product data

| General Information | |
|------------------------------------|-------------------|
| Driver included | Yes |
| Light source engine type | LED |
| | |
| Light Technical | |
| Luminous Flux | 1,500 lm |
| Luminous Efficacy (rated) (Nom) | 110 lm/W |
| Correlated Color Temperature (Nom) | 6500 K |
| Color rendering index (CRI) | >80 |
| Beam angle of light source | 120 degree(s) |
| Light source color | 865 cool daylight |
| Optic type | Beam angle 120° |
| Optical cover type | Polycarbonate |
| Luminaire light beam spread | 120° |
| | |
| Operating and Electrical | |
| Input Voltage | 130-320 V |
| Line Frequency | 50 Hz |
| | |

| Power Consumption | 13.5 W |
|---------------------------|---------------------------------|
| Power Factor (Fraction) | 0.95 |
| | |
| Temperature | |
| Ambient temperature range | 0 to +45 °C |
| | |
| Controls and Dimming | |
| Dimmable | No |
| | |
| Mechanical and Housing | |
| Housing Material | Aluminum die cast |
| Optic material | Polycarbonate |
| Optical cover material | Polycarbonate |
| Housing Color | White and black |
| Mounting device | Spring clip for recess mounting |
| Material | Aluminum |

GreenPerform Sleek

| Approval and Application | |
|--|---|
| Ingress protection code | IP20 [Finger-protected] |
| Mech. impact protection code | IK02 [0.2 J standard] |
| Surge Protection (Common/Differential) | Surge protection level until 2.5 kV |
| Protection class IEC | Safety class I |
| Flammability mark | For mounting on normally flammable surfaces |
| Warranty period | 2 years |
| | |
| Initial Performance (IEC Compliant |) |
| Initial chromaticity | <5 |
| Power consumption tolerance | +/-10% |
| | |
| Over Time Performance (IEC Compliant) | |
| Median useful life L70B50 | 50,000 hour(s) |

| Product Data | |
|---------------------------------|---------------------------|
| Order product name | DN296B LED15S-6500 PSU WH |
| Full product name | DN296B LED15S-6500 PSU WH |
| Order code | 919515812859 |
| Material Nr. (12NC) | 919515812859 |
| Numerator - Quantity Per Pack | 1 |
| Net Weight (Piece) | 0.280 kg |
| Numerator - Packs per outer box | 20 |
| | |

Dimensional drawing



© 2023 Signify Holding All rights reserved. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify. Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V.

www.lighting.philips.com 2023, April 15 - data subject to change